

Technical data sheet

Rauhfaserfarbe



Product description

- Characteristics:**
- Seamless wall and ceiling paint
 - With woodchip effect
 - Mat
 - Wash-resistant finish
 - Steam permeable
 - Good adhesion
 - Outstanding hiding power
 - Free of harmful emissions
 - Solvent-free

Material

- Application Area:** For interior use on good, solid new and old undergrounds such as stucco, concrete, gypsum board (without lignin marks).
- Binding Agent:** Acrylic copolymerisate
- Colour:** White
- Content of Solids:** Approx. 65 %
- Specific gravity:** 1.47 g/cm³
- pH value:** Approx. 9
- Diluting agent:** Water
- Viscosity:** Slightly thixotropic

JONAS Rauhfaserfarbe



Application Characteristics

Application:	Brush / roller / spray (funnel gun, screw pump or pressure tank according to manufacturer's specification).
Underground:	Needs to be clean, dry, and solid. Otherwise use JONAS Hydro-Haft- & Tiefgrund first to consolidate the underground. For underground treatment and application VOB, part C, DIN 18363 and the relevant BFS information must be observed.
Coating build-up:	Priming coat: dilute product with approx. 10 % water. Final coating: use product without dilution. Spraying: dilute product with approx. 5 - 10 % water.
Spreading rate per coating:	Roller: approx. 450 g/m ² for one coating. Spraying: approx. 900 g/m ² overall. (If necessary test on the wall).
Application temperature:	At least + 5°C (Degrees Celsius) for air and underground during application and drying.
Drying:	The surface of the coating is dry and can be painted over after 8 - 10 hours (at a temperature of 20 °C and a relative atmospheric humidity of 65 %).
Cleaning of tools:	Clean with water immediately after use.

General information

Storage:	Cool, but not freezing.
Shelf-life:	Can be stored for at least 6 months after date of filling (see additional sticker) if stored properly in the unopened original packaging.
Art.No. and description:	08 50 001 JONAS Rauhfaserfarbe
Packaging:	20 kg
Ingredients acc. to VdL RL01:	Resin dispersion, white pigment, calcium carbonate, silicate, organic filler, water, additives, preservatives, BIT/MIT.
Safety:	Please follow the instructions of the safety data sheet.
Labelling:	This product is not classified according to EU regulation No 1272/2008 [CLP].
Product-code:	BSW20
VOC content:	EU-Limit for the product Kat. A/a: 30 g/l (2010). This product contains < 1 g/l VOC.
Waste disposal:	Empty containers can be disposed for recycling. Any dried residues of material can be disposed of as construction waste or together with domestic garbage. Containers with liquid material residues must be disposed of according to local regulations. For further information, please contact your local waste authority.
Advice acc. to CLP:	Keep out of reach of children. Wear appropriate respiratory protection (full mask / half mask equipped with filter type A2/P2). Avoid eating, drinking and smoking during use of the product. Ensure good ventilation during and after application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains or water courses. Contains: 1,2-Benzisothiazol-3(2H)-on / 2-Methyl-2H-isothiazol-3-on. May produce an allergic reaction. Advice for people suffering from isothiazolinone allergy under phone-no.: +49(0)2058/789-0.